

Pure Decor™
LINER

Production Unit: Gävle mill

Product Description

The light coated Pure Decor™ kraftliner is a preferred material for high quality post-print and pre-print. High strength ensures light, strong packages with minimised washboarding. Pure Decor™ is produced from 100% virgin fibres.

Grammages

120, 145, 160 g/m²

Approvals

Pure Decor™ is produced in compliance with FDA and BfR packaging norms.

Certifications

Gävle Mill is certified in accordance with ISO 9001, ISO 14001, ISO 50001 and FSSC 22000.

Property	Unit					Method
Grammage	g/m ²		120	145	160	ISO 536
Thickness	µm		145	180	195	ISO 534
Scott Bond	J/m ²		350	350	350	TAPPI T569
Burst strength	kPa		580	730	780	ISO 2759
SCT	CD	kN/m	2,8	3,2	3,6	ISO 9895
Tensile Stiffness	MD	kN/m	1250	1250	1300	ISO 1924
	CD	kN/m	600	600	700	
Roughness PPS-10	PS	µm	1,3	1,4	1,5	ISO 8791-4
Gloss	PS	%	45	45	45	TAPPI 2470
Brightness	PS	%	80	80	80	ISO 2470
Whiteness D65	PS	%	80	82	82	ISO 11475
Cobb	PS	g/m ²	34	34	34	ISO 535
	RS	g/m ²	38	38	38	
Moisture	%		7,0	7,0	7,0	ISO 287

MD = Machine Direction

CD = Cross Direction

PS = Print Side

RS = Reverse Side

Test climate: 50% RH, 23°C

The table shows typical data for a range of grammages.