

Pure Decor™ LINER

Production Unit: Gävle Mill

Product Description

The light coated Pure Decor™ kraftliner is a preferred material for high quality post-print.
High strength ensures light, strong packages with minimised washboarding.
Pure Decor™ is produced from 100% virgin fibres.

Grammages

120, 145, 160g/m²

Approvals

Pure Decor™ is produced in compliance with FDA and BfR packaging norms.

Certification

Gävle mill is certified in accordance with ISO 9001
ISO 14001, ISO 50001 and FSSC 22000

Property	Unit					Method
Grammage	g/m ²		120	145	160	ISO 536
Caliper	Microns		145	180	195	ISO 534
Bursting Strength	kPa		600	750	800	ISO 2759
SCT	kN/m	CD	2,9	3,5	4,0	ISO 9895
Tensile Stiffness	kN/m	MD	980	1250	1300	ISO 1924-3
	kN/m	CD	500	600	700	
Roughness PPS-10 TS	Microns	PS	1,3	1,4	1,5	ISO 8791-4
Gloss	%	PS	45	45	45	TAPPI T480
Brightness	%	PS	80	80	80	ISO 2470
Whiteness D65	%	PS	80	82	82	ISO 11475
Cobb 60	g/m ²	PS	34	34	34	ISO 535
	g/m ²	RS	38	38	38	
Moisture	%		7,0	7,0	7,0	ISO 287

MD = Machine Direction

CD = Cross Direction

PS = Printing Side

RS = Reverse Side

Test climate: 50% RH, 23C

The table shows typical values for a range of products

