



MediCrepe

CREPED MG KRAFT PAPER

Production Unit: Beetham

End uses

BillerudKorsnäs MediCrepe is a wet strength crepe paper with conformability in conjunction with good drape characteristics.

It offers high water repellency, good strength and barrier properties.

Suitable for sterilisation by steam or ETO gas.

Grammage

45 g/m²

Available in White (465) & Green (466).

MediCrepe is produced from pure, white Kraft pulp and consists entirely of primary virgin fibre.

Approvals

MediCrepe is produced in compliance with Bfr and FDA packaging norms.

Certification

Beetham mill is certified in accordance with ISO 9001, ISO 14001 and BS OHSAS 18001

Materials

Property	Unit		Value		Method
Grammage	g/m ²		45		ISO 538
Tensile strength	N/15mm kN/m *	MD	40	2.7*	ISO 1924-3
		CD	20	1.3*	
Wet Tensile strength	N/15mm kN/m *	MD	9	0.6*	ISO 3781
		CD	5	0.3*	
Elongation	%	MD	9		ISO 1924-3
pH Aqueous hot extract	pH		6.5		ISO 6588
Water repellency	s	MG	18		EN 868
		RS	18		
Drape	cm	MD	11.0		EN 868
		CD	11.5		

MD = Machine Direction CD = Cross Direction MG = MG side RS = Reverse Side Test climate: 50% RH, 23C Issue: 5 Rev:2 2015-07

The table shows typical values.

* indicates derived value, for information only.